


Manufacturer:  
KZWM OGNIОCHRON S.A.  
ul. Krakowska 83c, 34-120 Andrychów, Poland  
Phone +48 33 875 10 70, Fax +48 33 875 10 77  
e-mail: export@ogniochron.eu

[www.ogniochron.eu](http://www.ogniochron.eu)

**ogniochron**  
KZWM OGNIОCHRON S.A.

## Application

Designed especially for protection of cars, motor boats and sailing, camping etc.



## Basic features

- Cylinder diameter 86 mm.
- Easy and ergonomic operation.
- Fast and effective in extinguishing.
- Economical maintenance and service.
- Construction of the valve enables temporary interruption of extinguishing.
- Possibility of multiple refilling.
- Cylinder of fire extinguisher covered with polyester paint, resistant to UV radiation.

## Quality and safety

Manufactured according to requirements of domestic and EU markets on the basis of certified quality system ISO 9001. Fulfills requirements of European Standard EN3 and Safety Directive PED 2014/68/UE.

CE  
0062




BENOR



## Technical data

Extinguishing efficiency	34B C
Weight of extinguishing agent	1 kg
Working agent	16 g CO <sub>2</sub>
Operation time	min. 6 s
Cylinder test pressure	25 bar
Operating temperature	-30 °C / +60 °C
Total weight	1,9 kg
Fire under voltage	1000 V
Total height (A)	295 mm
Cylinder diameter (B)	86 mm



## Powder extinguisher

# GP-1z BC/AP

