

Manufacturer:

OGNIOCHRON S.A.

ul. Przemysłowa 42, 34-120 Andrychów, Poland

tel.: +48 33 875 10 70 ext. 161, e-mail: export@ogniochron.eu

www.ogniochron.eu

ogniochron

Application

Mobile trolley carbon dioxide extinguisher AS-50 x B is used particularly in power industry, petrochemical and chemical industries for protection of warehouses of liquids and flammable gases, paint houses, industrial halls. The largest efficiency is obtained during extinguishing of fire in compartments.



Basic features

- Deep-drawn steel cylinder, covered with durable paint layer.
- 5-meters long rubber hose with snow horn at the end, making directing of extinguishing agent easier.
- Comfortable trolley, enabling easy and quick transportation of device.
- Easy maintenance and reliable operation.


Quality and safety

Manufactured according to the requirements of national and EU markets on the basis of certified quality system ISO 9001. Fulfills requirements of the standard PN-EN 1866-1 as well as the Safety Directive PED 2014/68/UE.



Technical data

Extinguishing efficiency	144B
Weight of extinguishing agent	50 kg
Operation time	36 s
Cylinder test pressure	320 bar
Operating temperature	-20 °C/+60 °C
Total weight	~188 kg
Fire under voltage	245000 V
Total height (A)	1250 mm
Cylinder diameter (B)	510 mm



Carbon dioxide movable extinguisher 50 kg

AS-50x B

