

Manufacturer:

OGNIOCHRON S.A.

ul. Przemysłowa 42, 34-120 Andrychów, Poland

tel.: +48 33 875 10 70 ext. 161, e-mail: export@ogniochron.eu

[www.ogniochron.eu](http://www.ogniochron.eu)

## Application

Designed for protection of community buildings, office rooms, production facilities, warehouses for flammable liquids, airports.

FF fire extinguishers contain a new type of extinguishing foam without fluorine and PFAS, making them completely biodegradable and environmentally neutral.



## Basic features

- Easy and ergonomic in operation.
- Fast and effective in extinguishing.
- Economical maintenance and service.
- Cut-off valve behind the pressure indicator makes control of fire extinguisher easier.
- Construction of the valve enables temporary interruption of extinguishing.
- Possibility of multiple refilling.
- Cylinder of fire extinguisher covered with polyester paint, resistant to UV radiation.
- Interior of cylinder protected with anticorrosive layer.


## Quality and safety

Manufactured according to requirements of domestic and EU markets on the basis of certified quality system ISO 9001. Fulfils requirements of European Standard EN 3 and Safety Directive PED 2014/68/UE.



## Technical data

|                               |                |
|-------------------------------|----------------|
| Extinguishing efficiency      | 34A 183B       |
| Weight of extinguishing agent | 9 l            |
| Working agent                 | N <sub>2</sub> |
| Operation time                | min. 15 s      |
| Cylinder test pressure        | 27 bar         |
| Operation pressure            | 15 bar         |
| Operating temperature         | 0 °C/+60 °C    |
| Total weight                  | ~14 kg         |
| Fire under voltage            | 1000 V         |
| Total height (A)              | 576 mm         |
| Cylinder diameter (B)         | 185 mm         |



# ogniochron

## Fluorine-free foam extinguisher

### GPN-9x AB/FF

FLUORINE **FREE**

