

Manufacturer:

OGNIOCHRON S.A.

ul. Przemysłowa 42, 34-120 Andrychów, Poland

tel.: +48 33 875 10 70 ext. 161, e-mail: export@ogniochron.eu

www.ogniochron.eu

ogniochron

Application

This fire extinguisher effectively extinguishes Class A fires involving solid materials, leaving no residue after use.

Additionally, it can be used for the controlled cooling and mitigation of the effects of fires involving devices equipped with lithium-ion batteries, such as electric scooters and bicycles, as well as battery-powered gardening equipment (e.g., lawnmowers).



Basic features

- Easy and ergonomic in operation.
- Fast and effective in extinguishing.
- Economical maintenance and service.
- Cut-off valve behind the pressure indicator makes control of fire extinguisher easier.
- Construction of the valve enables temporary interruption of extinguishing.
- Cylinder of fire extinguisher covered with polyester paint, resistant to UV radiation.
- Interior of cylinder protected with anticorrosive layer.


Quality and safety

Manufactured according to requirements of domestic and EU markets on the basis of certified quality system ISO 9001. Fulfills requirements of Safety Directive PED 2014/68/UE.



Technical data

Extinguishing efficiency	27A
Amount of extinguishing agent	9 l
Working agent	N ₂
Operating time	15 s
Cylinder test pressure	27 bar
Operation pressure	15 bar
Temperature range	+5 °C/+60 °C
Total weight	~14 kg
Fire under voltage	1000 V
Total height (A)	576 mm
Cylinder diameter (B)	185 mm
For extinguishing batteries:	from 500 Wh up to 750 Wh



Foam extinguisher (for Li-ion batteries)

GW-9x A/VER-DIS

VER•DIS

