

Manufacturer:

OGNIOCHRON S.A.

ul. Przemysłowa 42, 34-120 Andrychów, Poland

tel.: +48 33 875 10 70 ext. 161, e-mail: export@ogniochron.eu

www.ogniochron.eu

ogniochron

Application

Perfectly extinguishing without leaving any traces after usage of extinguishing agent. Recommended for protection of public spaces, such as offices, archives, schools, medical clinics, lawyer offices.



Basic features

- Absolutely environmental friendly.
- Easy and ergonomic operation.
- Fast and effective in extinguishing.
- Economical maintenance and service.
- Cut-off valve behind the pressure indicator makes control of fire extinguisher easier.
- Construction of the valve enables temporary interruption of extinguishing.
- Possibility of multiple refilling.
- Cylinder of fire extinguisher covered with polyester paint, resistant to UV radiation.


Quality and safety

Manufactured according to requirements of domestic and EU markets on the basis of certified quality system ISO 9001. Fulfills requirements of European Standard EN3 and Safety Directive PED 2014/68/UE.



Technical data

Extinguishing efficiency	13A 40F
Weight of extinguishing agent	6 l
Working agent	N ₂
Operation time	min. 9 s
Cylinder test pressure	27 bar
Operation pressure	15 bar
Operating temperature	+5 °C/+60 °C
Total weight	~9,3 kg
Fire under voltage	1000 V
Total height (A)	493 mm
Cylinder diameter (B)	160 mm



Water mist extinguisher GWM-6x AF/MP

