

Manufacturer:

OGNIOCHRON S.A.

ul. Przemysłowa 42, 34-120 Andrychów, Poland

tel.: +48 33 875 10 70 ext. 161, e-mail: export@ogniochron.eu

www.ogniochron.eu

ogniochron

Application

Designed to protect devices with lithium-ion batteries like: laptops, tablets, powerbanks, etc.

An innovative extinguishing agent based on vermiculite dispersion quickly cools the battery and extinguishes the flames. The airtight shell blocks oxygen and prevents the spread of fire.



Basic features

- Easy and ergonomic in operation.
- Fast and effective in extinguishing.
- Economical maintenance and service.
- Cut-off valve behind the pressure indicator makes control of fire extinguisher easier.
- Construction of the valve enables temporary interruption of extinguishing.
- Cylinder of fire extinguisher covered with polyester paint, resistant to UV radiation.
- Interior of cylinder protected with anticorrosive layer.

Quality and safety


Manufactured according to requirements of domestic and EU markets on the basis of certified quality system ISO 9001. Fulfills requirements of Safety Directive PED 2014/68/UE.

CE
0062



Technical data

Amount of extinguishing agent	2 l
Working agent	N ₂
Operating time	19 s
Cylinder test pressure	27 bar
Operation pressure	15 bar
Temperature range	+5 °C/+60 °C
Total weight	~4,1 kg
Fire under voltage	1000 V
Total height (A)	368 mm
Cylinder diameter (B)	110 mm



Extinguishing device for lithium battery

VER-DIS 2x

VER•DIS

