

Manufacturer:

OGNIOCHRON S.A.

ul. Przemysłowa 42, 34-120 Andrychów, Poland

tel.: +48 33 875 10 70 ext. 161, e-mail: export@ogniochron.eu

www.ogniochron.eu

ogniochron

Application

Designed to protect devices with lithium-ion batteries like: scooters and electric bikes, and battery-powered garden equipment such as lawn mowers. An innovative extinguishing agent quickly cools the battery and extinguishes the flames.



- Easy and ergonomic in operation.
- Fast and effective in extinguishing.
- Economical maintenance and service.
- Cut-off valve behind the pressure indicator makes control of fire extinguisher easier.
- Construction of the valve enables temporary interruption of extinguishing.
- Cylinder of fire extinguisher covered with polyester paint, resistant to UV radiation.
- Interior of cylinder protected with anticorrosive layer.

Quality and safety


Manufactured according to requirements of domestic and EU markets on the basis of certified quality system ISO 9001. Fulfills requirements of Safety Directive PED 2014/68/UE.

CE
0062



Technical data

Amount of extinguishing agent	9 l
Working agent	N ₂
Operating time	50 s
Cylinder test pressure	27 bar
Operation pressure	15 bar
Temperature range	+5 °C/+60 °C
Total weight	~14 kg
Fire under voltage	1000 V
Total height (A)	576 mm
Cylinder diameter (B)	185 mm
For extinguishing batteries:	from 500 Wh up to 750 Wh



Extinguishing device for lithium battery

VER-DIS 9x

VER•DIS

